



SPECIFICATIONS	
EXCITATION MAX. (V)	+24V
OVERLOAD CAPACITY (%F.S.)	200
CROSSTALK (%F.S.)	2.5
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +100
COMPENSATED TEMP. RANGE (°C)	10 TO 70
MASS (KG) NOT INCLUDING ADAPTOR	0.58

CABLE #1	
COLOR	FUNCTION
BLUE	+24V
WHITE/BLUE	GND
WHITE/BROWN	RX
BROWN	TX

LED STATUS	SENSOR STATUS
OFF	POWER OFF
FLIKER	WORK PROPERLY
ON	ABNORMAL

SRI- SUNRISE INSTRUMENTS
www.srisensor.com

	F _x (N)	F _y (N)	F _z (N)	M _x (Nm)	M _y (Nm)	M _z (Nm)
CAPACITY	400	400	400	24	24	24
RESOLUTION	0.13	0.13	0.13	0.0025	0.0025	0.0025

SIX AXIS CIRCULAR LOAD CELL
D81MM F400N, Ethernet TCP/IP

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M4313N3B	REV. B
--	----------	-----------